



(11) Publication number : **0 596 750 A1**

(12) **EUROPEAN PATENT APPLICATION**

(21) Application number : 93308867.6

(51) Int. Cl.⁵ : **B65F 5/00, B65G 53/26**

(22) Date of filing : 05.11.93

(30) Priority : 05.11.92 JP 76276/92
 16.04.93 JP 89986/93
 29.06.93 JP 158946/93
 06.09.93 JP 221423/93
 06.09.93 JP 221424/93

(43) Date of publication of application :
 11.05.94 Bulletin 94/19

(84) Designated Contracting States :
 DE DK FR GB SE

(71) Applicant : **SHINMAYWA INDUSTRIES, LTD.**
 5-25 Kosone-cho 1-chome
 Nishinomiya-shi, Hyogo (JP)


(72) Inventor : **Maruo, Shozo, c/o Special Purpose Truck Sales**
 Div. of ShinMaywa Ind., Ltd., 2-43, Shitte 3-chome
 Tsurumi-ku, Yokohama (JP)
 Inventor : **Okazaki, Akio, c/o Special Purpose Truck Sales**
 Div. of ShinMaywa Ind., Ltd., 2-43, Shitte 3-chome
 Tsurumi-ku, Yokohama (JP)
 Inventor : **Usui, Hitoshi, c/o Special Purpose Truck Sales**
 Div. of ShinMaywa Ind., Ltd., 2-43, Shitte 3-chome
 Tsurumi-ku, Yokohama (JP)
 Inventor : **Matsuo, Yasunori, c/o Special Purpose Truck Sales**
 Div. of ShinMaywa Ind., Ltd., 2-43, Shitte 3-chome
 Tsurumi-ku, Yokohama (JP)

(74) Representative : **Brown, Kenneth Richard et al**
R.G.C. Jenkins & Co. 26 Caxton Street
London SW1H 0RJ (GB)

(54) **Garbage suction/transfer unit.**

(57) Disclosed herein is a garbage suction/transfer unit for sucking and transferring collected garbage to a garbage truck (21) having a vacuum suction unit (22) and a suction pipe (23). The garbage suction/transfer unit comprises a garbage container (20) having a garbage outlet on its lower portion, a garbage transfer pipe (25) having an end which is connected to the garbage outlet of the garbage container and another end which is connected to the suction pipe (23) of the garbage truck (21), an air intake pipe (26) for introducing air into the garbage container (20), and a bypass pipe (28) having an end which is connected to an upper portion of the garbage container (20) and another end which is connected to the garbage transfer pipe (25) for forming a bypass suction passage. When garbage stored in the garbage container (20) blocks the garbage outlet, air which is introduced from the air intake pipe (26) flows toward the bypass pipe (28). Due to such a flow of the air, the garbage is relieved from a concentrating state, thereby opening the garbage outlet.

FIG.2



BACKGROUND OF THE INVENTION

Field of the Invention

The present invention relates to a garbage suction/transfer unit for sucking garbage which is stored in a garbage container installed in a multiple dwelling house or the like and transferring the same to a garbage truck comprising a vacuum suction unit and a suction pipe.

Description of the Background Art

Japanese Patent Laying-Open No. 4-272002, which was laid open to the public on September 28, 1992, discloses a garbage suction/transfer unit. Fig. 1 illustrates this garbage suction/transfer unit.

A garbage container 1 is installed in a multiple dwelling house or the like. The garbage container 1 has a garbage inlet 10 and a garbage outlet 12 on its upper and lower portions. A garbage transfer pipe 5 extending in the ground has an end which is connected to the garbage outlet 12 of the garbage container 1, and another end which is connected to a docking station 6.

A garbage truck 2 comprises a vacuum suction unit 3 and a suction pipe 4. A lower end of the suction pipe 4 is connected with the garbage transfer pipe 5 at the docking station 6.

In the state shown in Fig. 1, a closing gate 11 is in a closed position to seal the garbage container 1.

An air intake pipe 7 having a valve 8 is connected to the lower portion of the garbage container 1. Garbage in the garbage container 1 is transferred to the garbage truck 2 as follows.

First, the vacuum suction unit 3 of the garbage truck 2 is driven to negatively pressurize the garbage container 1 to a prescribed negative pressure value. Thereafter the valve 8 is opened to introduce air into the garbage container 1 through the air intake pipe 7. Garbage stored in the garbage container 1 is sucked and transferred with the as-introduced air to a garbage tank 14 which is provided in the garbage truck 2 through the garbage transfer pipe 5 and the suction pipe 4.

However, the aforementioned conventional garbage suction/transfer unit has the following problems:

As shown in Fig. 1, a connecting portion 15 of the garbage container 1 is converged toward the garbage outlet 12, in order to adapt the size of the garbage outlet 12 to the diameter of the garbage transfer pipe 5. When a large quantity of the garbage is gathered in the garbage outlet 12 to pass through the same at the same time, therefore, the garbage may clog the garbage outlet 12 to disable suction/transfer thereof. In this case, the garbage collector must release the garbage outlet 12 from such clogging of the garbage while temporarily stopping the sucking operation.

This leads to deterioration of working efficiency, as well as a large burden on the garbage collector.

In the example shown in Figs. 1, a single garbage container 1 is connected to the garbage transfer pipe 5. On the other hand, a plurality of such garbage containers (not shown) may be connected to a single garbage transfer pipe 5. In this case, a discharge gate 9 is provided on the garbage transfer pipe 5 communicating with each garbage container 1. In order to suck/transfer garbage from such a plurality of garbage containers, the garbage containers are not simultaneously but successively subjected to sucking operations one by one. Therefore, only the discharge gate 9 corresponding to a garbage container requiring a sucking operation is opened.

When the garbage transfer pipe 5 is provided with the aforementioned discharge gate 9, projecting and depressing portions are formed in the vicinity of the discharge gate 9 to hinder an operation for transferring garbage.

Further, the conventional garbage suction/transfer unit may continuously carry out a sucking operation in vain after the garbage container is completely evacuated. Such a sucking operation is wasteful.

SUMMARY OF THE INVENTION

An object of the present invention is to provide a garbage container which can simply release a garbage outlet from clogging of garbage.

Another object of the present invention is to provide a garbage suction/transfer unit which can efficiently suck and transfer garbage from a garbage container with no energy loss.

Still another object of the present invention is to provide a garbage suction/transfer unit which can avoid energy loss by grasping whether or not a garbage container stores garbage.

A garbage suction/transfer unit according to the present invention comprises a garbage container, a docking station, a garbage transfer pipe, an air intake pipe, and a bypass pipe. The garbage container has a garbage inlet and a garbage outlet on its upper and lower portions respectively. The docking station receives a suction pipe of a garbage truck. The garbage transfer pipe has an end which is connected to the garbage outlet of the garbage container, and another end which is connected to the suction pipe of the garbage truck at the docking station. The air intake pipe is adapted to introduce air into the garbage container. The bypass pipe has an end which is connected to the upper portion of the garbage container and another end which is connected to the garbage transfer pipe, to form a bypass suction passage.

Garbage which is introduced from the garbage inlet and stored in the garbage container is sucked and transferred to a garbage tank of the garbage truck in the following manner: First, a vacuum suction

unit of the garbage truck is driven to negatively pressurize the garbage container. Thereafter air is introduced into the garbage container through the air intake pipe. The garbage stored in the garbage container is sucked and transferred with the as-introduced air to the garbage tank of the garbage truck through the garbage transfer pipe.

When a large quantity of garbage concentrates to the garbage outlet of the garbage container to block the same during the aforementioned sucking operation, the air which is introduced through the air intake pipe cannot pass through the garbage outlet. In this case, the air upwardly flows toward the bypass pipe, which connects the upper portion of the garbage container and the garbage transfer pipe. The garbage stored in the garbage container is upwardly sucked due to such an upward flow of the air. The part of the garbage clogging the garbage outlet is also upwardly sucked, and relieved from concentration at the garbage outlet. Consequently, the garbage outlet is so opened that the garbage is again sucked and transferred to the garbage transfer pipe through the garbage outlet. Even if the garbage stored in the garbage container concentrates to block the garbage outlet, therefore, the garbage outlet is automatically released from such a blocked state by the upward flow of the air toward the bypass pipe according to the present invention. Thus, the sucking operation can be continuously carried out to efficiently collect the garbage.

According to one aspect of the present invention, the bypass pipe is provided with valve means for opening/closing its air passage. This valve means preferably comprises pressure detection means for detecting the pressure in the garbage transfer pipe, a movable valve element which is arranged in the bypass pipe, and valve element driving means for bringing the movable valve element to an open position in response to the pressure, detected by the pressure detection means, which is reduced below a prescribed level.

While the garbage stored in the garbage container is sucked and transferred with the air through the garbage outlet, the pressure in the garbage transfer pipe will not be reduced below the prescribed level. In this case, the movable valve element closes the air passage of the bypass pipe. Therefore, the air which is introduced into the garbage container entirely flows through the garbage outlet, to cause no energy loss.

When a large quantity of garbage concentrates to block the garbage outlet, on the other hand, the air flow to the garbage transfer pipe is stopped and hence the pressure in the garbage transfer pipe is reduced below the prescribed level. In this case, the movable valve element which is arranged in the bypass pipe is brought into the open position, whereby the air contained in the gas container flows toward the bypass pipe. Due to the upward flow of the air, the

garbage stored in the garbage container is upwardly sucked to release the garbage outlet from the blocked state. Thus, the garbage outlet is so opened that the garbage is again sucked and transferred to the garbage transfer pipe through the garbage outlet. Consequently, the pressure in the garbage transfer pipe exceeds the prescribed level, whereby the movable valve element provided in the bypass pipe is brought into a closed position.

According to another aspect of the present invention, the air intake pipe comprises a first intake pipe which is connected to the garbage container in the vicinity of the garbage outlet, and a second intake pipe which is connected to the garbage container at a position upwardly separated from the first intake pipe. In this case, the garbage suction/transfer unit preferably comprises a first valve for opening/closing an air passage of the first intake pipe, a second valve for opening/closing an air passage of the second intake pipe, a first pressure detector for detecting an internal pressure around a connected portion between the first intake pipe and the garbage container, a second pressure detector for detecting an internal pressure around a connected portion between the second intake pipe and the garbage container, a third pressure detector for detecting the pressure in the garbage transfer pipe, and control means for controlling opening/closing operations of the first and second valves on the basis of information detected in the respective pressure detectors.

Preferably, the control means brings the first and second valves into open and closed positions respectively in starting of a sucking operation. Further, the control means brings the first and second valves to closed and open positions respectively when difference between pressure values detected by the first and second detectors is reduced below a prescribed level. In addition, the control means terminates the sucking operation when difference between the pressure values detected by the second and third pressure detectors is reduced below a prescribed level.

Due to the aforementioned control means, the garbage which is stored in the garbage container is efficiently sucked and transferred successively from a lower part thereof.

According to still another aspect of the present invention, the air intake pipe comprises a stem pipe, a first branch pipe, and a second branch pipe. The first branch pipe is branched from the stem pipe, and connected to the garbage container in the vicinity of the garbage outlet. The second branch pipe is also branched from the stem pipe, and connected to the garbage container at a position upwardly separated from the first branch pipe. In this aspect, the stem pipe is preferably provided with a valve for opening/closing its air passage. According to this aspect, air is introduced through the branch pipes which are located in upper and lower portions, whereby the air

can be effectively pressed against garbage which is vertically stacked in the garbage container.

According to a further aspect of the present invention, the garbage suction/transfer unit comprises garbage detection means for detecting presence/absence of garbage in the garbage container, and control means for terminating a sucking operation in response to absence of garbage detected by the garbage detection means. According to this aspect, a termination period of the sucking operation is so correctly controlled that it is possible to avoid energy loss and reduce the working time.

According to a further aspect of the present invention, the garbage suction/transfer unit comprises an inlet pipe having a lower end which is connected to the garbage inlet, and an inlet gate for opening/closing a passage of the inlet pipe. In starting of a sucking operation, the inlet gate is controlled to be brought into a closed position. In termination of the sucking operation, on the other hand, the inlet gate is controlled to be brought into an open position. According to this aspect, the inlet gate is brought into the closed position during the sucking operation, whereby it is possible to prevent air from flowing through the garbage inlet.

According to a further aspect of the present invention, the air intake pipe comprises a first intake pipe which is connected to the garbage container in the vicinity of the garbage outlet, a second intake pipe which is connected to the garbage container at a position upwardly separated from the first intake pipe, a first valve for opening/closing an air passage of the first intake pipe, and a second valve for opening/closing an air passage of the second intake pipe. According to this aspect, the first valve is first brought into an open position so that the second valve is thereafter brought into an open position in a sucking operation. In termination of the sucking operation, on the other hand, the second valve is first brought into a closed position, so that the first valve is thereafter brought into a closed position.

According to a further aspect of the present invention, the air intake pipe upwardly feeds air from a lower portion in the garbage container. According to this aspect, the garbage is stirred or loosened by such an upward flow of the air. Thus, it is possible to effectively prevent the garbage outlet from blocking caused by concentration of a large quantity of garbage.

When such an air intake pipe for upwardly feeding air from a lower portion is employed, further, a garbage entrance inhibitor is preferably provided on an opening of the air intake pipe for inhibiting the garbage from entering the air intake pipe.

The foregoing and other objects, features, aspects and advantages of the present invention will become more apparent from the following detailed description of the present invention when taken in

conjunction with the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

- 5 Fig. 1 illustrates a conventional garbage suction/transfer unit;
- Fig. 2 illustrates a garbage suction/transfer unit according to an embodiment of the present invention;
- 10 Fig. 3 illustrates a principal part of the embodiment of the present invention in an enlarged manner;
- Fig. 4 illustrates a principal part of another embodiment of the present invention;
- 15 Fig. 5 illustrates a principal part of still another embodiment of the present invention;
- Fig. 6 illustrates a principal part of a further embodiment of the present invention;
- 20 Fig. 7 is a flow chart showing a first half of a garbage sucking operation;
- Fig. 8 is a flow chart showing a second half of the garbage sucking operation;
- Fig. 9 illustrates a principal part of a further embodiment of the present invention;
- 25 Fig. 10 illustrates a principal part of a further embodiment of the present invention;
- Figs. 10A and 10B are views corresponding to a cross section taken along line A-A;
- Fig. 11 illustrates a principal part of a further embodiment of the present invention;
- 30 Fig. 12 illustrates a principal part of a further embodiment of the present invention;
- Fig. 13 is a flow chart showing a first half of a garbage sucking operation;
- 35 Fig. 14 is a flow chart showing a second half of the garbage sucking operation;
- Fig. 15 is a flow chart showing another exemplary second half of the garbage sucking operation;
- 40 Fig. 16 illustrates a principal part of a further embodiment of the present invention;
- Fig. 17 illustrates an exemplary garbage entrance inhibitor;
- Fig. 18 illustrates another exemplary garbage entrance inhibitor;
- 45 Fig. 19 is a partially fragmented sectional view showing a connected portion of an air intake pipe;
- Fig. 20 illustrates an exemplary opening of the air intake pipe; and
- 50 Fig. 21 illustrates another exemplary opening of the air intake pipe.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

Referring to Fig. 2, a garbage truck 21 comprises a vacuum suction unit 22, a suction pipe 23, and a garbage tank 32. The structure of this garbage truck

21 is described later in detail.

A garbage container 20 is installed in a proper place of a multiple dwelling house or the like. Referring to Fig. 3, the garbage container 20 has a garbage inlet 29 and a garbage outlet 30 on its upper and lower portions respectively. In order to define the garbage inlet 29, a closing member 31 is rotatably provided on the upper portion of the garbage container 20. When the closing member 31 is closed, the garbage container 20 is sealed as shown in Fig. 3. As shown in Fig. 3, further, the lower portion of the garbage container 20 is converged toward the garbage outlet 30. Therefore, garbage 33 is smoothly moved toward the garbage outlet 30.

A garbage transfer pipe 25 extending in the ground has an end which is connected to the garbage outlet 30 of the garbage container 20, and another end which is connected to a lower end of the suction pipe 23 at a docking station 24.

An air intake pipe 26 having a valve 27 is connected to a lower portion of the garbage container 20 close to the garbage outlet 30. This air intake pipe 26 is adapted to introduce air into the garbage container 20 in a sucking operation. The air intake pipe 26 is connected to an air source (not shown) of the garbage truck 21 through the docking station 24. Alternatively, the air source may be provided on the garbage container 20. The valve 27 is so opened/closed as to control introduction of air.

The feature of the present invention resides in provision of a bypass pipe 28. This bypass pipe 28 has an end which is connected to the upper portion of the garbage container 20 and another end which is connected to the garbage transfer pipe 25, to define a bypass suction passage.

The structure of the garbage truck 21 is now described in further detail.

The vacuum suction unit 22 comprises a suction passage 34 having an end which is connected to the garbage tank 32 and another end which is open to the atmospheric air, a water scrubber 35 which is provided in the suction passage 34, a blower 36 which is provided in a portion of the suction passage 34 closer to the end being open to the atmospheric air than the water scrubber 35, and a silencer 37 which is provided in a portion of the suction passage 34 closer to the end being open to the atmospheric air than the water scrubber 35.

When an engine of the garbage truck 21 is driven, the blower 36 is driven in response to the engine speed. Thus, the atmosphere in the garbage container 20 is negatively pressurized through the garbage transfer pipe 25.

A pressure sensor 38 is provided in a portion of the suction passage 34 between the water scrubber 35 and the blower 36, in order to detect the value of the negative pressure which is applied by the blower 36.

The garbage tank 32 comprises a door 39 on its rear end. This door 39 is formed to be rearwardly open about its upper edge. A horizontally slidable discharge plate (not shown) is arranged in the garbage tank 32. This discharge plate is so moved as to rearwardly discharge garbage which is introduced into the garbage tank 32.

The suction pipe 23 includes a swing pipe 40 which is connected to the garbage tank 32 on its upper portion to be rotatable about a vertical axis, a flexible pipe 41 which is connected to the swing pipe 40, a hinged pipe 42 which is hingeably connected to the flexible pipe 41, an expansion pipe 43 which is connected to the hinged pipe 42, another flexible pipe 44 which is connected to the expansion pipe 43, and a forward end portion 45 which is connected to the flexible pipe 44. A support member 46 supports the forward end portion 45 in movement of the vehicle. Further, a support frame 47 supports the hinged pipe 42.

In order to collect garbage, the garbage truck 21 is stopped in the vicinity of the docking station 24. The forward end portion 45 of the suction pipe 23 is moved to a proper position by swinging of the swing pipe 40, hinging of the hinged pipe 42, expansion of the expansion pipe 43 and the like, so that the same is connected to a forward end portion 48 of the garbage transfer pipe 25 at the docking station 24.

The garbage truck 21 is provided with a control unit (not shown). This control unit receives manipulate signals from various control switches, a detection signal from the pressure sensor 38 and the like, as well as detection signals from various detectors. Further, signal cables (not shown) are installed through the docking station 24, in order to transfer the signals between the control unit of the garbage truck 21 and detectors provided on the garbage container 20 etc. The control unit controls movements of the vacuum suction unit 22 and the suction pipe 23 of the garbage truck 21 and an operation of the valve 27 for opening/closing the air passage of the air intake pipe 26, on the basis of the manipulate signals and the detection signals. The control unit and a manipulation unit may alternatively be provided on the garbage container 20.

The operation of the garbage suction/transfer unit is now described.

The garbage 33 which is introduced through the garbage inlet 29 is stored in the garbage container 20. In order to collect the garbage 33 which is stored in the garbage container 20, the garbage truck 21 is first stopped in the vicinity of the docking station 24. Then, the forward end portion 45 of the suction pipe 23 is connected to the forward end portion 48 of the garbage transfer pipe 25 at the docking station 24.

The blower 36 is driven while opening the valve 27. Thus, the garbage 33 stored in the garbage container 20 is sucked and transferred to the garbage

tank 32 through the garbage transfer pipe 25, with air which is introduced through the air intake pipe 26.

When the garbage 33 stored in the garbage container 20 concentrates to the garbage outlet 30 to block the same during the aforementioned sucking operation, the air which is introduced through the air intake pipe 26 upwardly flows toward the bypass pipe 28, as shown by arrows in Fig. 3. Due to such an upward flow of the air, the garbage 33 is upwardly sucked in the garbage container 20 and released from the concentrating state, to finally relieve the garbage outlet 30 from clogging. Consequently, the garbage outlet 30 is so opened that the garbage 33 is sucked and transferred to the garbage tank 32 through the garbage outlet 30 and the garbage transfer pipe 25, with the air introduced through the air intake pipe 26.

Due to provision of the aforementioned bypass pipe 28, it is possible to automatically relieve the garbage outlet 30 from clogging of the garbage 33. Thus, it is possible to continuously carry out the garbage sucking operation, thereby efficiently collecting the garbage 33.

In the embodiment shown in Figs. 2 and 3, a single garbage container 20 is connected to a single garbage transfer pipe 25. Alternatively, a plurality of garbage containers may be connected to a single garbage transfer pipe 25. In this case, the respective garbage containers are negatively pressurized and thereafter the valve 27 of a garbage container to be subjected to garbage suction is opened, so that garbage can be sucked and collected from only the garbage container which is connected to this opened valve 27. Thus, it is not necessary to provide a discharge gate on the garbage transfer pipe 25, dissimilarly to the conventional garbage suction/transfer unit. In the conventional garbage suction/transfer unit which is provided with a discharge gate, projecting and depressing portions are defined in the vicinity of the discharge gate to hinder transfer of garbage. However, no such projecting and depressing portions are defined in the embodiment of the present invention. Thus, it is possible to smoothly suck/transfer garbage.

Fig. 4 illustrates a principal part of another embodiment of the present invention. Numerals identical to those of the first embodiment indicate the same or corresponding elements. The feature of the embodiment shown in Fig. 4 resides in that a valve mechanism 50 is provided on a bypass pipe 28, in order to open/close its air passage. The valve mechanism 50 comprises a valve element 51 which is provided to be rotatable about a central axis, a coupling member 52 which is connected to the valve element 51, a weight 53 which is mounted on an end of the coupling member, an air cylinder 54, and a throttle valve 57.

The air cylinder 54 has a rod 56, whose forward end is connected to the coupling member 52.

In the state shown in Fig. 4, the valve element 51 closes the air passage in the bypass pipe 28. When the rod 56 of the air cylinder 54 is extended from this state, the valve element 51 opens the air passage, as shown by phantom lines. The weight 53 is formed to be slidable along arrow B. Therefore, it is possible to adjust the force acting on the valve element 51 by adjusting the position of the weight 53.

A piston chamber 55a of the air cylinder 54 is opened to the atmospheric air. On the other hand, a rod chamber 55b communicates with a garbage transfer pipe 25 through the throttle valve 57. When the garbage transfer pipe 25 is negatively pressurized, therefore, the rod chamber 55b is also negatively pressurized through the throttle valve 57. Consequently, large pressure difference is caused between the rod chamber 55b and the piston chamber 55a, to extend the rod 56. When the force for extending the rod 56 exceeds the force of the weight 53 holding the valve element 51 at the closed position, the rod 56 upwardly raises the weight 53, to finally bring the valve element 51 to the open position shown by phantom lines. Thus, it is possible to bring the valve element 51 to the open position when the garbage transfer pipe 25 is negatively pressurized below a desired pressure level, by adjusting the position of the weight 53.

When a garbage sucking operation is normally carried out, the valve element 51 closes the air passage of the bypass pipe 28.

When garbage stored in a garbage container 20 concentrates to a garbage outlet 30 to block the same, the garbage transfer pipe 25 is negatively pressurized to a higher level than that in normal garbage suction. When the pressure in the garbage transfer pipe 25 is reduced below a prescribed level such that a pressure value at a point A in Fig. 4 is below -1000 mmAq, for example, a check valve mechanism of the throttle valve 57 is opened to negatively pressurize the rod chamber 55b. Thus, the rod 56 is extended against the weight 53, to bring the valve element 51 into the open position and open the air passage.

When the valve element 51 is brought into the open position, air which is introduced from an air intake pipe 26 upwardly flows toward the bypass pipe 28, similarly to the aforementioned embodiment. Due to the upward flow of the air, garbage is released from a concentrating state to open the garbage outlet 30. Thus, a normal garbage sucking operation is started so that the pressure in the garbage transfer pipe 25 exceeds the aforementioned prescribed level. Consequently, the pressure in the rod chamber 55b of the air cylinder 54 is also increased to reduce the pressure difference between the rod chamber 55b and the piston chamber 55a. Thus, the rod 56 is retracted by the weight 53. At this time, air gradually flows into the rod chamber 55b through a throttle

mechanism of the throttle valve 57. Finally the valve 51 is brought into a closed position.

In the embodiment shown in Fig. 4, the valve element 51 is opened only when the garbage outlet 30 is blocked. In other words, the valve 51 is in the closed position in a normal sucking operation, to shut the air passage of the bypass pipe 28. In the normal sucking operation, therefore, no part of the air which is introduced from the air intake pipe 26 flows through the bypass pipe 28, so that the air can be entirely adapted to transfer garbage.

Fig. 5 illustrates a principal part of still another embodiment of the present invention. Also in this embodiment, a bypass pipe 28 is provided with valve means. This valve means comprises a valve element 51 which is rotatably provided in the bypass pipe 28, a rotary solenoid 58, and a pressure sensor 59. The pressure sensor 59 detects the pressure in a garbage transfer pipe 25. When the pressure value detected by the pressure sensor 59 is reduced below a prescribed pressure level, the rotary solenoid 58 operates to bring the valve element 51 to an open position.

Fig. 6 illustrates a principal part of a further embodiment of the present invention. According to this embodiment, an air intake pipe for introducing air into a garbage container 20 comprises a first intake pipe 61, a second intake pipe 62, and a third intake pipe 63. The first intake pipe 61 is connected to the garbage container 20 in the vicinity of a garbage outlet 30. The second intake pipe 62 is connected to the garbage container 20 at a position which is upwardly separated from the first intake pipe 61 by a prescribed distance. The third intake pipe 63 is connected to the garbage container 20 at a position which is upwardly separated from the second intake pipe 62 by a prescribed distance. The intake pipes 61, 62 and 63 are provided with first, second and third valves V1, V2 and V3 respectively. These valves V1 to V3 are opened/closed by actuators (not shown).

The embodiment shown in Fig. 6 is further provided with a first pressure detector P1 for detecting an internal pressure around a connected portion between the first intake pipe 61 and the garbage container 20, a second pressure detector P2 for detecting an internal pressure around a connected portion between the second intake pipe 62 and the garbage container 20, and a third pressure detector P3 for detecting an internal pressure around a connected portion between the third intake pipe 63 and the garbage container 20. In this embodiment, sensors of the pressure detectors P1 to P3 detect the pressure in the garbage container 20. Alternatively, the sensors provided in the respective pressure detectors P1 to P3 may detect pressures in the intake pipes 61 to 63. The embodiment shown in Fig. 6 is further provided with a pressure detector PD for detecting the pressure in the garbage transfer pipe 25.

The values of the pressures detected by the re-

spective pressure detectors P1, P2, P3 and PD are inputted in a control unit (not shown). The control unit drives the actuators on the basis of the as-received pressure information, to control operations for opening/closing the respective valves V1, V2 and V3.

With reference to flow charts shown in Figs. 7 and 8, the opening/closing operations of the valves V1, V2 and V3 carried out by the aforementioned control unit are now described in more concrete terms.

First, the first valve V1 is brought into an open position and the second and third valves V2 and V3 are brought into closed positions at steps S1 and S2, to start a sucking operation. After a lapse of a prescribed time of t seconds (step S3), a determination is made at a step S4 as to whether or not difference between the pressure values detected by the first pressure detector P1 and the pressure detector PD is in excess of 1000 mmAq.

If the pressure difference is in excess of 1000 mmAq, it is recognized that garbage is present around the connected portion between the first intake pipe 61 and the garbage container 20, and the process is returned to the step S2. The garbage sucking operation is continuously carried out while introducing air from the first valve V1.

If a determination is made at the step S4 that the pressure difference is less than 1000 mmAq, on the other hand, it is recognized that garbage is sucked and transferred from around the connected portion between the first intake pipe 61 and the garbage container 20, and the process is advanced to a step S5.

At the step S5, the second valve V2 is brought into an open position and the first and third valves V1 and V3 are brought into closed positions. After a lapse of the prescribed time of t seconds in this state (step S6), a determination is made at a step S7 as to whether or not difference between the pressure values detected by the second pressure detector P2 and the pressure detector PD is in excess of 1000 mmAq. If the determination is of YES, the process is advanced to a step S8.

At the step S8, a determination is made as to whether or not difference between the pressure values detected by the second pressure detector P2 and the pressure detector PD is in excess of 3000 mmAq. If the determination is of YES, it is recognized that a large quantity of garbage is still present in a portion below the connected portion between the second intake pipe 62 and the garbage container 20, and the process is returned to the step S2, to carry out the steps S2 to S7. If the determination is of NO, on the other hand, the process is returned to the step S7, to continuously carry out the sucking operation while introducing air into the garbage container 20 from the second intake pipe 62.

If a determination is made at the step S7 that the pressure difference is less than 1000 mmAq, the process is advanced to a step S9.

At the step S9, the third valve V3 is brought into an open position and the first and second valves V1 and V2 are brought into the closed positions. After a lapse of the prescribed time of t seconds (step S10), a determination is made at a step S11 as to whether or not difference between the pressure values detected by the third pressure detector P3 and the pressure detector PD is in excess of 1000 mmAq. If the determination is of YES, the process is advanced to a step S12.

At the step S12, a determination is made as to whether or not the aforementioned pressure difference is in excess of 3000 mmAq. If the determination is of YES, it is recognized that a large quantity of garbage is present in a portion below the connected portion between the third intake pipe 63 and the garbage container 20, and the process is returned to the steps S2 to carry out the aforementioned steps S2 to S11. If the determination is of NO, on the other hand, the process is returned to the step S11, to continuously carry out the sucking operation while introducing air into the garbage container 20 through the third intake pipe 63.

If a determination is made at the step S11 that the pressure difference is less than 1000 mmAq, the sucking operation is terminated after a lapse of a set time of t_0 seconds (steps S13 and S14).

As hereinabove described, it is possible to efficiently suck and transfer garbage which is stored in the garbage container 20 successively from a lower part by controlling the opening/closing operations of the first, second and third valves V1, V2 and V3 on the basis of the pressure values detected by the pressure detectors P1, P2, P3 and PD. Thus, it is also possible to increase the size of the garbage container 20.

Fig. 9 illustrates a principal part of a further embodiment of the present invention. According to this embodiment, an air intake pipe for introducing air into a garbage container 20 comprises a stem pipe 65, a first branch pipe 66, a second branch pipe 67, and a third branch pipe 68. The first branch pipe 66 is connected to the garbage container 20 at a portion close to a garbage outlet 30 thereof. The second branch pipe 67 is connected to the garbage container 20 at a position which is upwardly separated from the first branch pipe 66. The third branch pipe 68 is connected to the garbage container 20 at a position which is upwardly separated from the second branch pipe 67. The stem pipe 65 is provided with a valve V for opening/closing its air passage. In a sucking operation, it is possible to suck and transfer garbage which is stored in the garbage container 20 successively from a lower part since air is introduced from the vertically arranged three branch pipes 66, 67 and 68.

Fig. 10 illustrates a principal part of a further embodiment of the present invention. According to this embodiment, an air intake pipe for introducing air into a garbage container 20 comprises a stem pipe 69, and

two branch pipes 70 and 71 which are branched from the stem pipe 69. The stem pipe 69 is provided with a valve V for opening/closing its air passage. The two branch pipes 70 and 71 are vertically separated from each other. In a sucking operation, therefore, it is possible to suck and transfer garbage which is stored in the garbage container 20 successively from a lower part, similarly to the embodiment shown in Fig. 9.

With regard to connection between the branch pipes 70, 71 and the garbage container 20, either structure as shown in Fig. 10A or Fig. 10B may be adopted. According to the structure as shown in Fig. 10A, the air is introduced into the garbage container 20 in a tangential direction and therefore, a spiral air stream is produced in the garbage container 20. Thus, the concentration of garbage is relieved.

In each of the aforementioned embodiments of the present invention, the garbage container 20 includes a vertical wall upwardly extending from the garbage outlet 30 and an inclined wall, which is opposite to the vertical wall, obliquely upwardly extending from the garbage outlet 30. The angle of inclination of the inclined wall with respect to a horizontal plane is preferably within a range of 45 to 60°. Thus, the lower portion of the garbage container 20 is converged toward the garbage outlet 30, so that it is possible to smoothly move the garbage which is stored in the garbage container 20 toward the garbage outlet 30.

Fig. 11 illustrates a principal part of a further embodiment of the present invention. According to this embodiment, a garbage container 20 is provided with left and right side walls 72 and 73 obliquely upwardly extending from a garbage outlet 30. A vertically extending partition 74 is arranged at a central portion of the garbage container 20.

Fig. 12 illustrates a principal part of a further embodiment of the present invention. According to this embodiment, an inlet pipe 87 is connected to an upper surface of a garbage container 20. A lower end of the inlet pipe 87 communicates with a garbage inlet 86. Garbage is introduced into the garbage container 20 through the inlet pipe 87. As shown in Fig. 12, an inlet gate 88 is provided on a lower portion of the inlet pipe 87, in order to open/close a passage of the inlet pipe 87. An air cylinder 89 controls movement of the inlet gate 88.

A detector (not shown) such as a limit switch is arranged in the vicinity of the inlet gate 88, in order to detect opening/closing thereof.

First and second intake pipes 80 and 81 are provided in order to introduce air into the garbage container 20. The first intake pipe 80 is connected to the garbage container 20 at a position close to a garbage outlet 30. The second intake pipe 81 is connected to the garbage container 20 at a position which is upwardly separated from the first intake pipe 80. The first intake pipe 80 is provided with a first valve 82

which is opened/closed by a first air cylinder 84. The second intake pipe 81 is provided with a second valve 83 which is opened/closed by the second air cylinder 85.

The air cylinders 84, 85 and 89 are connected to an air source (not shown) through air hoses (not shown). The air source may be installed in a garbage truck, or in the vicinity of the garbage container 20. When the air source is installed in the garbage truck, the air hoses extending from the air cylinders 84, 85 and 89 are connected to those extending from the garbage truck at a docking station.

Detectors (not shown) such as limit switches are arranged in the vicinity of the first and second valves 82 and 83 for detecting opening/closing thereof.

The garbage container 20 is provided on its upper portion with a garbage detector 90 for detecting presence/absence of garbage in the garbage container 20. This garbage detector 90 is prepared from an optical sensor for projecting light toward the garbage outlet 30 from the upper portion of the garbage container 20, for example. When such an optical sensor is employed, absence of garbage is determined if there is no obstacle within a constant distance (between the upper surface of the garbage container 20 and the garbage outlet 30, for example).

The embodiment shown in Fig. 12 is so controlled that a sucking operation is terminated when the garbage detector 90 detects absence of garbage. Such control means preferably also controls opening/closing operations of the first and second valves 82 and 83 and the inlet gate 88.

With reference to Figs. 13 and 14, the control operation of this embodiment is now described.

In order to suck and transfer garbage which is stored in the garbage container 20, the garbage truck is first stopped in the vicinity of the docking station, so that a suction pipe of the garbage truck is connected with a garbage transfer pipe 25 at the docking station (step S1).

An operating device is started at a step S2, so that the inlet gate 88 is brought into a closed position at a step S3. The closed state of the inlet gate 88 is detected by the detector at a step S4, so that the process is advanced to a step S5. At the step S5, a blower of the garbage truck is driven to negatively pressurize the garbage container 20.

When the garbage container 20 reaches a previously set negative pressure value (varied with the size of the garbage container 20 etc. but generally set at 2000 to 4000 mmAq) at a step S6, the process is advanced to a step S7. At the step S7, the first valve 82 is brought into an open position, to introduce air into the garbage container 20 through the first intake pipe 80. The air which is introduced through the first intake pipe 80 is sucked and transferred with the garbage to a garbage tank of the garbage truck through the garbage outlet 30 and the garbage transfer pipe

25.

When a prescribed time elapses after the first valve 82 is brought into the open position, the second valve 83 is brought into an open position at a step S8. In this state, air is introduced into the garbage container 20 through both of the first and second intake pipes 80 and 81. The air thus introduced into the garbage container 20 is sucked and transferred with the garbage to the garbage tank of the garbage truck through the garbage outlet 30 and the garbage transfer pipe 25.

As hereinabove described, the second valve 83 is opened after the first valve 82 is opened for the prescribed time, so that a part of the garbage which is stored in the vicinity of the garbage outlet 30 is discharged from the same. Following this discharge operation, an intermediate part of the garbage is loosened to gradually fall toward the garbage outlet 30, so that the garbage is discharged successively from a lower part. Then the second valve 83 is so opened that an upper part of the garbage is loosened and guided to the garbage outlet 30. Thus, a large quantity of garbage which is stored in the garbage container 20 is not simultaneously be gathered to the garbage outlet 30 but can be smoothly sucked and transferred.

The garbage stored in the garbage container 20 is collected in the garbage tank of the garbage truck in the aforementioned manner (step S9), and after a lapse of a prescribed time (step S10), the second valve 83 is brought into a closed position at a step S11 and then the first valve 82 is brought into a closed position at a step S12.

At a step S13, the garbage detector 90 detects presence/absence of garbage in the garbage container 20. If presence of garbage is detected, the process is returned to the step S5 to carry out the garbage sucking operation of the steps S5 to S12 again.

If absence of garbage is detected, on the other hand, the inlet gate 88 is opened at a step S14, to terminate the sucking operation (step S15). Thereafter the suction pipe of the garbage truck is separated from the docking station at a step S16.

As hereinabove described, presence/absence of garbage in the garbage container 20 is detected by the garbage detector 90 to control the termination period of the garbage sucking operation on the basis of the result of detection, whereby it is possible to avoid energy loss and reduce the working time. Further, the first valve 82 is closed after the second valve 83 is closed in termination of the garbage sucking operation, whereby air is introduced into a portion close to the garbage outlet 30 to a final stage for efficiently discharging garbage which is left in the vicinity of the garbage outlet 13.

The embodiment shown in Fig. 12 is also provided with a bypass pipe 28. Even if the garbage stored in the garbage container 20 concentrates to the gar-

bage outlet 30 to block the same, therefore, it is possible to automatically release the garbage outlet 30 from such a blocked state.

A plurality of the garbage containers 20 shown in Fig. 12 may be connected to a single garbage transfer pipe 25. In this case, the first and second valves 82 and 83 of the garbage container 20 to be subjected to a sucking operation are opened after the respective garbage containers 20 are negatively pressurized, so that garbage can be sucked and transferred only from the garbage container 20 having the opened valves 82 and 83. Namely, a step S131 is provided between the steps S13 and S14 as shown in Fig. 15, in order to determine whether or not the currently treated garbage container 20 is the final one. If the determination is of NO, the number of the garbage container 20 is updated at a step S132, and the process is returned to the aforementioned step S5. In the respective garbage containers 20, all inlet gates 88 are simultaneously opened/closed.

Fig. 16 illustrates a principal part of a further embodiment of the present invention. A garbage container 20 is provided on its upper portion with a garbage inlet opening 104. An inlet pipe 105 upwardly extends from the garbage inlet opening 104. A rotatable closing member 106 is provided on an upper portion of the inlet pipe 105. The closing member 106 defines a garbage inlet 107, which is exposed when the closing member 106 is anticlockwise rotated from the state shown in Fig. 16.

An inlet gate 108 is provided on a lower portion of the inlet pipe 105, to be opened/closed by an air cylinder 109. A detector (not shown) such as a limit switch is arranged in the vicinity of the inlet gate 108 to detect opening/closing thereof.

In the embodiment shown in Fig. 16, an air intake pipe 101 for introducing air into the garbage container 20 upwardly feeds air from a lower portion of the garbage container 20. In order to form such an air flow, it is preferable that the air intake pipe 101 obliquely upwardly extends as shown in Fig. 16 so that its upper end portion is connected to the garbage container 20. This air intake pipe 101 is provided with a valve 102 for opening/closing its air passage.

In order to inhibit garbage stored in the garbage container 20 from entering the air intake pipe 101, a garbage entrance inhibitor 103 shown in Fig. 17 is mounted on an opening of a connected portion between the air intake pipe 101 and the garbage container 20. The garbage entrance inhibitor 103 comprises a plurality of bar members 110 vertically extending in the form of a lattice. A surface of the garbage entrance inhibitor 103 is preferably rendered to be flush with an inner wall surface of the garbage container 20, so that the garbage stored in the garbage container 20 can smoothly fall toward the garbage outlet 30.

Fig. 18 illustrates another exemplary garbage

entrance inhibitor 111. This garbage entrance inhibitor 111 is in the form of a porous plate having a number of through holes 112. Alternatively, the garbage entrance inhibitor may be in the form of a mesh.

In the embodiment shown in Fig. 16, air which is introduced into the garbage container 20 through the air intake pipe 101 upwardly flows from a lower portion. The garbage is stirred or loosened by such an upward flow of the air, whereby the garbage can be smoothly discharged from the garbage container 20 through the garbage outlet 30.

The embodiment shown in Fig. 16 is also provided with a bypass pipe 28. Even if the garbage outlet 30 is blocked by the garbage, therefore, it is possible to automatically release the garbage outlet 30 from such a blocked state.

Figs. 19 and 20 illustrate a further exemplary air intake pipe 120. A vertically elongated opening 121 is defined in a connected portion between the air intake pipe 120 for introducing air into the garbage container 20 and the garbage container 20. Due to formation of the elongated opening 121, a region of the air which is introduced into the garbage container 20 is vertically elongated thereby vertically increasing a region for stirring or loosening the garbage stored in the garbage container 20. Therefore, it is possible to smoothly suck and transfer the garbage. The air intake pipe 120 shown in Fig. 19 is also provided with a valve 122 for opening/closing its air passage.

Fig. 21 illustrates another exemplary opening 121, which is defined in a connected portion between an air intake pipe and a garbage container, formed by a plurality of vertically arranged small holes 123.

According to the present invention, as hereinabove described, it is possible to efficiently suck garbage which is stored in a garbage container and transfer the same to a garbage tank of a garbage truck.

Although the present invention has been described and illustrated in detail, it is clearly understood that the same is by way of illustration and example only and is not to be taken by way of limitation, the spirit and scope of the present invention being limited only by the terms of the appended claims.

Claims

1. A garbage suction/transfer unit for sucking and transferring collected garbage to a garbage truck (21) having a vacuum suction unit (22) and a suction pipe (23), said garbage suction/transfer unit comprising:

a garbage container (20) having a garbage inlet (29) and a garbage outlet (30) on its upper and lower portions respectively;

a docking station (24) for receiving said suction pipe of said garbage truck;

- a garbage transfer pipe (25) having an end being connected to said garbage outlet of said garbage container and another end being connected to said suction pipe of said garbage truck at said docking station;
- an air intake pipe (26) for introducing air into said garbage container; and
- a bypass pipe (28) having an end being connected to said upper portion of said garbage container and another end being connected to said garbage transfer pipe, thereby forming a bypass suction passage.
2. The garbage suction/transfer unit in accordance with claim 1, wherein
said lower portion of said garbage container (20) is converged toward said garbage outlet (30).
 3. The garbage suction/transfer unit in accordance with claim 1, further comprising a valve (27) for opening/closing an air passage of said air intake pipe (26).
 4. The garbage suction/transfer unit in accordance with claim 1, further comprising valve means (50) for opening/closing an air passage of said bypass pipe (28).
 5. The garbage suction/transfer unit in accordance with claim 4, wherein
said valve means comprises:
pressure detection means (A) for detecting the pressure in said garbage transfer pipe (25),
a movable valve element (51) being arranged in said bypass pipe (28) to be movable between an open position for opening said air passage and a closed position for closing said air passage, and
valve element driving means (54) for bringing said movable valve member into said open position in response to reduction of the pressure being detected by said pressure detection means below a prescribed value.
 6. The garbage suction/transfer unit in accordance with claim 1, wherein
said air intake pipe comprises:
a first intake pipe (61) being connected to said garbage container (20) in the vicinity of said garbage outlet (30), and
a second intake pipe (62) being connected to said garbage container (20) at a position being upwardly separated from said first intake pipe.
 7. The garbage suction/transfer unit in accordance with claim 6, further comprising:

- a first valve (V1) for opening/closing an air passage of said first intake pipe (61),
a second valve (V2) for opening/closing an air passage of said second intake pipe (62),
a first pressure detector (P1) for detecting an internal pressure around a connected portion between said first intake pipe (61) and said garbage container (20),
a second pressure detector (P2) for detecting an internal pressure around a connected portion between said second intake pipe (62) and said garbage container (20),
a third pressure detector (PD) for detecting the pressure in said garbage transfer pipe (25), and
control means for controlling opening/closing operations of said first and second valves on the basis of information being detected by respective said pressure detectors.
8. The garbage suction/transfer unit in accordance with claim 7, wherein
said control means controls said operations for:
bringing said first and second valves (V1, V2) to open and closed positions respectively in starting of a sucking operation,
bringing said first and second valves (V1, V2) into closed and open positions respectively when difference between pressure values being detected by said first and third pressure detectors (P2, PD) is reduced below a prescribed value, and
terminating said sucking operation when difference between pressure values being detected by said second and third pressure detectors (P2, PD) is reduced below a prescribed value.
 9. The garbage suction/transfer unit in accordance with claim 1, wherein
said air intake pipe comprises:
a stem pipe (65),
a first branch pipe (66) being branched from said stem pipe to be connected to said garbage container in the vicinity of said garbage outlet, and
a second branch pipe (67) being branched from said stem pipe to be connected to said garbage container at a position being upwardly separated from said first branch pipe.
 10. The garbage suction/transfer unit in accordance with claim 9, further comprising a valve (V) for opening/closing an air passage of said stem pipe.
 11. The garbage suction/transfer unit in accordance with claim 1, wherein

said garbage container includes:
 a vertical wall vertically upwardly extending from said garbage outlet, and
 an inclined wall, being opposite to said vertical wall, obliquely upwardly extending from said garbage outlet.

12. The garbage suction/transfer unit in accordance with claim 1, further comprising:

garbage detection means (90) for detecting presence/absence of garbage in said garbage container, and

control means for terminating a sucking operation in response to absence of garbage being detected by said garbage detection means.

13. The garbage suction/transfer unit in accordance with claim 12, wherein

said garbage detection means includes an optical sensor (90) being arranged on an upper portion of said garbage container (20) for projecting light toward said garbage outlet.

14. The garbage suction/transfer unit in accordance with claim 12, further comprising:

an inlet pipe (87) having a lower end being connected to said garbage inlet (86), and

an inlet gate (88) for opening/closing a passage of said inlet pipe,

said control means controlling said operations for:

bringing said inlet gate into a closed position in starting of said sucking operation, and

bringing said inlet gate into an open position in termination of said sucking operation.

15. The garbage suction/transfer unit in accordance with claim 12, wherein

said air intake pipe comprises:

a first intake pipe (80) being connected to said garbage container (20) in the vicinity of said garbage outlet (30),

a second intake pipe (81) being connected to said garbage container (20) at a position being upwardly separated from said first intake pipe,

a first valve (82) for opening/closing an air passage of said first intake pipe (80), and

a second valve (83) for opening/closing an air passage of said second intake pipe (81).

16. The garbage suction/transfer unit in accordance with claim 15, wherein

said first valve (82) is first brought into an open position so that said second valve (83) is thereafter brought into an open position in starting of a sucking operation, and

said second valve (83) is first brought into a closed position so that said first valve (82) is

thereafter brought into a closed position in termination of said sucking operation.

17. The garbage suction/transfer unit in accordance with claim 14, wherein

a plurality of garbage containers are connected to said garbage transfer pipe,

all said inlet gates are brought into closed positions in starting of a sucking operation, and

all said inlet gates are brought into open positions in termination of said sucking operation.

18. The garbage suction/transfer unit in accordance with claim 1, wherein

said air intake pipe (101) upwardly feeds air from a lower portion in said garbage container (20).

19. The garbage suction/transfer unit in accordance with claim 18, wherein

said air intake pipe (101) obliquely upwardly extends so that its upper end portion is connected to said garbage container (20).

20. The garbage suction/transfer unit in accordance with claim 18, wherein

an opening (121) of said air intake pipe (120) is formed in a vertically elongated state.

21. The garbage suction/transfer unit in accordance with claim 18, wherein

said air intake pipe has a plurality of vertically arranged openings (123).

22. The garbage suction/transfer unit in accordance with claim 18, wherein

said air intake pipe has an opening which is provided with a garbage entrance inhibitor (103) for inhibiting garbage from entering said air intake pipe.

23. The garbage suction/transfer unit in accordance with claim 22, wherein

a surface of said garbage entrance inhibitor (103) is rendered to be flush with an inner wall surface of said garbage container (20).

24. The garbage suction/transfer unit according to claim 11, wherein said garbage container includes a further inclined wall (73) disposed on the opposite side of said vertical wall (74) to said first-mentioned inclined wall and inclined to the vertical in the opposite sense relative to said first-mentioned inclined wall, said inclined walls defining with said vertical wall adjacent garbage spaces sharing a common outlet (30) disposed beneath the base portion of said vertical wall

(74).

25. A garbage disposal installation in which there is provided a garbage container (20) having an upper inlet (29) through which garbage can fall into the container and a lower outlet (30) through which garbage can be removed from the container by suction through a garbage transfer passageway (25), and an air inlet (26) through which air can enter said container during such garbage removal, characterised by means (28) defining a bypass passageway for garbage removal in the event of partial or complete blockage of said lower outlet, said bypass passageway having an opening into said container at a position above the level of said air inlet (26), and communicating with said garbage transfer passageway (25).

20

25

30

35

40

45

50

55

FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG.8




FIG. 9




FIG. 10




FIG. 10A




FIG. 10B




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18




FIG.19




FIG.20





FIG.21





European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 93 30 8867

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cls)
D,A	PATENT ABSTRACTS OF JAPAN vol. 17, no. 64 (M-1364)(5693) 8 February 1993 & JP-A-04 272 002 (SHIN MEIWA IND CO LTD) 28 February 1992 * abstract *	1,25	B65F5/00 B65G53/26
A	HITACHI REVIEW vol. 39, no. 6, December 1990, TOKYO pages 387 - 392 XP000234643 INOUE & FUJITA 'Future urban refuse collection and transportation systems'	1,25	
A	US-A-4 900 200 (HARUMOTO ET AL.) * column 11, line 4 - line 11; figure 2 *	1,25	
A	EP-A-0 127 596 (WASSDAHL) * abstract; figures 1,2 *	1,25	
A	EP-A-0 297 145 (SHIMIZU CONSTRUCTION CO. LTD.) * figures 9,10 *	1,25	
			TECHNICAL FIELDS SEARCHED (Int.Cls)
			B65F B65G
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 4 February 1994	Examiner Martinez Navarro, A
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons * : member of the same patent family, corresponding document</p>			